

Pressure Unit Choices Available: psi—Bar—MPa
Analog Signal, NPN Limit Switch Available
Zero Offset
LCD Digital Display
ISO 9001

Technical Data

Peak Hold

zero adjustment

Accuracy: $\pm 0.5\%$ of full scale ($\pm 1\%$ of full scale for 15 & 50 psi)

LCD Display: 30X 14.5cm, with 4 digits

Dimension: 3", H11.5 X W4.5cm

Operating Temperature: -10 to 60°C

Over Pressure: 2 times of F.S.

Process Connections: 1/4" NPT Male, standard

Connection Material: SS316

Multiple Pressure Limit: Psi, Bar, MPa

Power Supply:10~30 VDC


Output Mode: 4~20mA with NPN limit switch



Range Table

Pressure Range	Accuracy	Resolution		
		PSI	Bar	MPa
15 PSI	Tpy. $\pm 1\%$ F.S.	0.01	0.001	0.001
50 PSI	Tpy. $\pm 1\%$ F.S.	0.01	0.001	0.001
100 PSI	Tpy. $\pm 0.5\%$ F.S.	0.01	0.001	0.001
200 PSI	Tpy. $\pm 0.5\%$ F.S.	0.1	0.01	0.001
300 PSI	Tpy. $\pm 0.5\%$ F.S.	0.1	0.01	0.001
500 PSI	Tpy. $\pm 0.5\%$ F.S.	0.1	0.01	0.001
1000 PSI	Tpy. $\pm 0.5\%$ F.S.	0.1	0.01	0.001
3000 PSI	Tpy. $\pm 0.5\%$ F.S.	0.1	0.1	0.01
5000 PSI	Tpy. $\pm 0.5\%$ F.S.	0.1	0.1	0.01

Dimensions



Ordering Information

DPG3000T	Code	Pressure Range			
		(1) 15psi (2) 50psi (3) 100psi (4) 200psi (5) 300psi (6) 500psi (7) 1000psi (8) 3000psi (9) 5000psi			
	Code	Connection port			
	U	1/4"NPT	S	Customized	
		Code	Power Supply		
	A	10~30 VDC			
		Code	Ouput Signal		
	(1) 4~20mA with NPN limit switch				
DPG3000T					Complete Ordering Code