


TEMPERATURE SWITCH EXPLOSION PROOF TYPE ETS3000X SERIES

CLASS I, GROUPS B, C & D
CLASS II, GROUPS E, F & G NEMA 4,7,9
Temperature: -200 ~ +650°C


Technical Data

Type	Liquid Filled Type	Gas Filled Type
Temperature Range	-70~+400°C	-200~650°C
Remote capillary length	20M max.	30M max.
Electric contact	1~2 contacts	
Microswitch type S.P.D.T.	Nominal operating voltage: 250 VAC max. Current: 5A max.	
Alternatively switch data	Nominal operating voltage: 28 VDC max. Current: 5A max.(ohmic load); 3A max. (inductive load) Contact material: Pure silver 999.9 Ambient temperature: -20°C ~ +70°C	
Explosion proof class	Class I, Groups B, C & D; Class II, Groups E, F & G; Class III	
Material of case & cover	Aluminum alloy die-casting	
Switch acting differential	±1.6~3% of F.S.	
Contact adjusting method	Internal adjusting method	
Conduit connection	¾" NPT(F)	
Process connection	½" or ¾" NPT Male	
Sensor material	wetted parts are all in SS316	

Dimensions



Minimum Inserting Length of Sensor Bulb



Range Selection Table

Liquid Filled Type	
Item	Adjustable Range (°C)
1	-70~+50
2	-50~+50
3	-30~+50
4	-30~+100
5	-10~+50
6	-10~+100
7	0~50
8	0~60
9	0~80
10	0~100
11	0~120
12	0~150
13	0~200
14	0~250
15	0~300
16	0~400

Gas Filled Type	
Item	Adjustable Range (°C)
1	-200~+50
2	-200~+100
3	-200~+150
4	-200~+200
5	-100~+100
6	-100~+150
7	-100~+200
8	-50~+300
9	-50~+400
10	-50~+500
11	-50~+600
12	0~100
13	0~150
14	0~200
15	0~250
16	0~300
17	0~400
18	0~500
19	0~650

OPTION.

1. Special range available upon request.
2. Special scale available upon request.
3. Special stem diameter and length available upon request.

Effective Bulb Insertion Length

Liquid Filled Type					
Outside Dimension d		Ø6	Ø8	Ø10	Ø12
Range °C					
1	-70~+50	130	90	80	80
2	-50~+50	156	100	90	90
3	-30~+50	195	110	90	90
4	-30~+100	120	90	80	80
5	-10~+50	260	120	110	110
6	-10~+100	142	90	80	80
7	0~50	312	140	120	120
8	0~60	312	140	120	120
9	0~80	195	110	90	90
10	0~100	156	100	90	90
11	0~120	130	90	80	80
12	0~150	104	80	70	70
13	0~200	78	80	70	70
14	0~250	63	80	70	70
15	0~300	53	80	70	60
16	0~400	39	70	60	60

Gas Filled Type					
Outside Dimension d		Ø6	Ø8	Ø10	Ø12
Capillary Length					
1	0~10m	150	100	80	80
2	11~30m	200	150	130	130

Ordering Information

Model	Type
ETS3000X-B	Bottom Connection Type
ETS3000X-C	Capillary Type
Code Measuring Range Please refer to the range selection table. e.g. 1 = Range is -70~+50°C Code Capillary Length (M) Please fill in the requested length. 0 only for ETS3000X-B Code Process Connection A (A) ½" NPT Male (B) ¾" NPT Male (O) option Code Stem Outside Dimensions (1) Ø6mm (2) Ø8mm (3) Ø10mm (4) Ø12mm (5) option Code Stem Length (mm) Please refer to bulb length table. Fill in the requested length.	
Complete Ordering Code	