


Series 200 & 300

## **Durablock® Solid Plastic Stationary Gages**

Suitable for Total Pressures Up to 100 psig, Temperatures Up to 150°F. Accuracy  $\pm 2\%$  of Full Scale (1% on Models 215, 244, 246 Only)



Dwyer® solid plastic stationary gages — or draft gages — are offered in inclined and vertical (well-type) styles for highly accurate laboratory or general industrial service, for measurement of low range gas and air pressures, positive, negative or differential. To assure the accuracy required in instruments of this type, all machining of bores and wells is to the highest standards of precision backed by Dwyer's years of experience in the fabrication of acrylic instruments.

## Over-Pressure Safety Traps Prevent Fluid Loss



Exclusive Dwyer® over pressure safety traps assure that over range pressures whether gradual or a sudden surge will not force the liquid out of the gage. Over pressures simply raises the float, force the Oring over the opening and seal the fluid in the gage. When pressure is reduced, float drops down releasing the Oring safety trap opens and the gage continues in operation.

Incline Type				
<b>31</b>				
	Range Inches			Weight
	of Water	Divisions	Length	lbs-oz.
200.5	.10-0-1.0	.01	8-1/4	3-11
201	.05-050	.01	5-1/2	2-12
202.5	.20-0-2.0	.01	8-3/4	4-7
209	.20-0-3.0	.02	8-3/4	4-11
215	.05-025	.005	6	2-14
244	0-4	.02	13-1/4	9-11
246	0-6	.02	20	13-14
Vertical or Well-Type				
300	0- 4	.10	4-1/2	2-5
306	0- 6	.10	7-3/4	3-3
308	0- 8	.10	9	3-7
310	0-10	.10	11-1/8	3-10

Note: Model 200.5 replaces Model 200. Model 202.5 replaces model 202.