

STAINLESS STEEL SAFETY VALVES

N9SP/N9-LSP

Technical Data

Low lift safety valves

Material: Body-CF8, Valve seat-CF8

Orifice size: 1/2"(15mm), 3/4"(20mm), 1"(25mm), 1 1/4"(32mm), 1 1/2"(40mm), 2"(50mm)

Working pressure: 2~10 kgf/cm² (28~150 psig), 11~20 kgf/cm² (156~285 psig)

Working temp.: -60°C~196°C


Working fluid: Noncorrosive gas, noncorrosive liquid, air, steam, corrosive gas, corrosive liquid, water, oil




Soft Seal

Dimensions

(unit:mm)



N9SP TYPE
Sealing 1/2"~2"



N9LSP TYPE
Lever 1/2"~2"

SEALING SERIES

ITEM	SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
A		142	164	200	232	256	283
Inlet B		1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Outlet C		1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Valve Seat Orifice D		15	20	25	32	40	50
E		29	36	40	50	54	66
F		49	55	67	79	86	96
Lift		0.52	0.76	1.00	1.28	1.52	2.00
Wt. kg		0.5	0.7	1.2	2.0	2.6	4.3

LEVER SERIES

ITEM	SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
A1		168	190	222	248	272	306
Wt. kg		0.6	0.8	1.3	2.0	2.7	4.6

Blowout Capacity Table

(unit:mm)

set pressure	orifice	Steam Blowout Cap. (kg/h)					
		1/2"(15)	3/4"(20)	1"(25)	1 1/4"(32)	1 1/2"(40)	2"(50)
1 kgf/cm ²		18.4	39.2	67.90	111.3	156.9	271.7
2 kgf/cm ²		27.7	59.1	102.4	167.7	236.6	409.5
3 kgf/cm ²		37.0	79.0	136.9	224.2	316.2	547.4
4 kgf/cm ²		46.3	98.9	171.3	280.7	395.8	685.2
5 kgf/cm ²		55.7	118.8	205.8	337.1	475.4	823.1
6 kgf/cm ²		65.0	138.7	240.2	393.6	555.0	960.9
7 kgf/cm ²		74.3	158.7	274.7	450.1	634.7	1099
8 kgf/cm ²		83.6	178.6	309.2	506.5	714.3	1237
9 kgf/cm ²		92.9	198.5	343.6	563.0	793.9	1374
10 kgf/cm ²		102.3	218.4	378.1	619.5	893.5	1512
11 kgf/cm ²		111.6	238.3	412.5	675.9	953.2	1650
12 kgf/cm ²		120.9	258.2	447.0	732.4	1033	1788
13 kgf/cm ²		130.2	278.1	481.5	788.8	1112	1926
14 kgf/cm ²		139.5	298.0	515.9	845.3	1192	2064
15 kgf/cm ²		148.9	317.9	550.4	901.8	1272	2202
16 kgf/cm ²		158.2	337.8	584.9	958.3	1351	2239
17 kgf/cm ²		167.5	357.7	619.3	1014.7	1431	2477
18 kgf/cm ²		176.8	377.6	653.8	1071.2	1511	2615
19 kgf/cm ²		186.1	397.5	688.2	1127.6	1590	2753
20 kgf/cm ²		195.4	417.4	722.7	1184.1	1670	2891

General Material List

NO.	Type	N9SP SEALING	N9-LSP LEVER
1.	Valve Body	CF8	
2.	Valve Seat	CF8	
3.	Disc	SUS304 or CF8	
3-1.	Soft Seal	Teflon (PTFE)	
4.	Spring	SUS304	
5.	Stem	SUS304	
Working Pressure		2~10 kgf/cm ² 11~20 kgf/cm ²	
Working Temp.		-60°C~196°C	
Working Fluid		Noncorrosive gas, noncorrosive liquid, corrosive gas, corrosive liquid, air, steam, water, oil	Noncorrosive gas, corrosive gas, air, steam

Ordering Information

N9SP / N9-LSP	Code	Valve Seat
	0	CF8 + PTFE
		Code Pressure Rating
	1	2~10 kg/cm ² 2 11~20 kg/cm ²
		Code Size
		(A)1/2" NPT (B)3/4" NPT (C)1" NPT (D)1 1/4" NPT (E)1 1/2" NPT (F)2" NPT
		Complete Ordering Code